DIRECTLY DRIVEN PLANETARY RIGID AXLES







PATENTED SELF-COOLED TURBO BRAKE




DIFFERENTIAL LOCKS MDDL OR NOSPIN® OR DOG CLUTCH OR LIMITED SLIP



DIRECT MOTOR ATTACHMENT WITH GEAR DRIVE

TYPE	SAP 34	SAP 55	SAP 75	SAP 85
Ratio	49.54	23.98	49.48 - 96.35	75.62
Static axle load up to [kN]	310	320	420	579
Dynamic axle load [kN]	260	200	300	579
Max. speed [kph]	6	20	15	8
Parking brake	Optional	Optional	Optional	Optional
Service brake	Optional	Optional	Optional	Optional
Max. input torque [Nm]	800	1300	700	360
Input RPM	2000	3400	3500	1780
Axle width [mm]	1123	2570	1485 - 2084	1676
Flange-to-flange [mm]	800	2100	1107 - 1826	1186
Bolt circle [mm]	225	335	425	500
Driven by	Directly attached gearbox / hydrostatic or electrical driveline			
Differential locks	MDDL / NoSpin* / dog clutch / limited slip			





DIRECTLY DRIVEN PLANETARY RIGID AXLES

Product features:

- > Very compact design
- > Mounting options: fixed or oscillating
- > Various hydraulic or electric motor sizes and models can be attached











NAF is the expert for power transmission, traction and load capacity on mobile working machines. Our gears and axles create a substantial competitive advantage in the heavy-duty off-highway industry. As a system partner we have been mastering the tasks of our market-leading customers since 1960 and invest 5% of our annual turnover into research and development.

As our customer you benefit directly from our passion for innovation that guarantees your success.



AT HOME ON 3 CONTINENTS

46

Supplied countries worldwide

620

Employees in total

35.000 m²

38,000

of production space in 17 halls

Components sold each year

15

Patents and protected innovations

35

Employees working in R&D/PDP

Headquarters and production

NAF Neunkirchener Achsenfabrik AG Weyhausenstrasse 2 91077 Neunkirchen am Brand Germany

T: +49 9134 702-0 F: +49 9134 702-640 info@nafaxles.com

For more information about our branches in North America, France, Germany (HQ), Russia & China visit:

